



THIS IS GREENFIBER® BLOW-IN NATURAL FIBER CELLULOSE INSULATION

Application Coverage Chart		19.05 lbs (8.64 kg)				INS541LD	
R-Value at 75° F Mean Temp. Valor de resistencia termica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor minimo (en pulgadas)		Net Coverage (no adjustment for framing) Recubrimiento neto (Sin compensacion para el entramado)			Gross Coverage (based on 2" x 6" framing on 16" centers) Recubrimiento Bruto (Bosado en armazón de 5.08 cm x 15.24 cm (2" x 6" en centro de 40.64 cm (16"))	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad minima de bolsas por 1,000 ples cuadrados	Minimum Weight per Sq. Ft. (lbs/ft ²) Peso minimo por pie cuadrado (lb/pie ²)	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad minima de bolsas por 100 metros cuadrados
R 13	4.29	3.86	56.0	17.9	0.340	61.8	16.2
R 19	6.19	5.57	36.7	27.2	0.519	40.0	25.0
R 22	7.12	6.41	31.1	32.2	0.613	33.5	29.8
R 25	8.05	7.25	26.8	37.2	0.710	28.7	34.9
R 30	9.57	8.62	21.7	46.1	0.878	22.9	43.6
R 38	11.97	10.77	16.4	61.1	1.164	17.1	58.5
R 49	15.20	13.68	12.0	83.5	1.591	12.4	80.7
R 60	18.37	16.53	9.3	108.1	2.059	9.5	105.0

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 19.05 LBS USING THE GREENFIBER MONARCH BLOWING MACHINE. SETTINGS ARE NOT ADJUSTABLE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT MUST BE INSTALLED DRY. THIS COVERAGE CHART DOES NOT APPLY TO FLOOR APPLICATIONS. DO NOT ADD WATER TO THIS PRODUCT. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 18.1 LBS.

READ THIS BEFORE YOU BUY

What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:

GreenFiber Corporate Office
2500 Distribution Street, Suite 200
Charlotte, NC 28203

(p) 800.228.0024 (f) 704.379.0685
(e) GreenFiber.info@greenfiber.com
www.greenfiber.com

MANUFACTURING LOCATIONS:

Albany, NY
Charlotte, NC
Delphos, OH
Norfolk, NE
Phoenix, AZ
Salt Lake City, UT
Tampa, FL
Waco, TX

